



Shieldex[®] Med-tex P70

115090213070



Raw Material	79 % Polyamide + 21 % Elastomer
Type of knit	Stretch-Tricot
Metal Plated	Silver
Material Composition	(75 % PA / 21 % EL / 4 % Ag) ± 10 %
Stretch	Double stretch direction / elongation warp 160-210 % / weft 75-115 %
Total Weight	100 g/m ² ± 18 %
Total Thickness	0.42 mm ± 15 %
Roll Width	135 ± 5 cm
Roll Length	Max. 36 m
Temperature Range	-30 °C to 80 °C
Storage and Handling	According to our care and handling instructions
Compliance and Certification	DIN EN ISO 9001:2015, REACH, RoHS

Alterations Reserved 16.09.2021/13 – The above information has been compiled from our manufacturer area according to the latest state of development and application technology. Since application and further processing are beyond our control, no liability of the producer can be derived from the contents of the data sheet. All deviant or transcending data sheet information must be confirmed in written form by the manufacturer. Our general terms and conditions apply in all cases. All previous data sheets are invalid with the publication of this data sheet. Please note our handling and storage instructions as well accessible at www.shieldex.de.

Physical Address
V Technical Textiles, Inc
320 South Main Street
Newark, NY 14513

Mailing Address
V Technical Textiles, Inc
4502 State Rt. 31
Palmyra, NY 14522

Contact
Phone: (315)-597-1674
Fax: (315)-597-6687
info@vtechtextiles.com

