



Shieldex[®] 100 μ Monofil

2002120100

Material	Polyamide / Nylon 6.6
Metal Plated	99.9 % Pure Silver
Yarn count raw	90/1 -4/+8 dtex
Yarn count silverized	100/1 \pm 5 dtex
Electrical Resistivity	<100 Ω /cm
Yield	100.000 m/kg \pm 5 %
Tenacity	42 \pm 5 cN/tex
Elongation / Break	33 % \pm 5
Make Up	On cones 230 mm 3° 30
Packaging	Average 400 g net yarn per cone 15 or 30 cones per carton
Storage and Handling	According to our care and handling instructions
Compliance and Certification	OEKO-TEX [®] Standard 100, DIN EN ISO 9001:2015, REACH, RoHS

Alterations Reserved 15.10.21/08 – The above information has been compiled from our manufacturer area according to the latest state of development and application technology. Since application and further processing are beyond our control, no liability of the producer can be derived from the contents of the data sheet. All deviant or transcending data sheet information must be confirmed in written form by the manufacturer. Our general terms and conditions apply in all cases. All previous data sheets are invalid with the publication of this data sheet. Please note our handling and storage instructions as well accessible at www.shieldex.de.

Physical Address
V Technical Textiles, Inc
320 South Main Street
Newark, NY 14513

Mailing Address
V Technical Textiles, Inc
4502 State Rt. 31
Palmyra, NY 14522

Contact
Phone: (315)-597-1674
Fax: (315)-597-6687
info@vtechtextiles.com

