



## Shieldex<sup>®</sup> Wrapped Yarn - coaxial

200471011717 Preliminary



<b>Material</b>	Nylon 6.6
<b>Core Material</b>	117/17 2 ply HCB TPU
<b>Wrapped Material</b>	117/17 2 ply HCB
<b>Metal Plated</b>	99.9 % Pure Silver
<b>TPU Coating</b>	Thermoplastic Polyurethane (TPU) transparent
<b>+ B Coating</b>	Nitrile rubber as additional protective coating
<b>Yarn count silverized</b>	3.290 dtex ± 5 %
<b>Electrical Resistivity</b>	< 300 Ω/m
<b>Yield</b>	3000 m /kg ± 10 %
<b>Tenacity</b>	44 ± 5 cN
<b>Elongation / Break</b>	23 % ± 5
<b>Make Up</b>	8 inch cross bobbin
<b>Packaging</b>	On request
<b>Storage and Handling</b>	According to our care and handling instructions
<b>Compliance and Certification</b>	DIN EN ISO 9001:2015, REACH, RoHS

**Alterations Reserved 04.11.21/01** – The above information has been compiled from our manufacturer area according to the latest state of development and application technology. Since application and further processing are beyond our control, no liability of the producer can be derived from the contents of the data sheet. All deviant or transcending data sheet information must be confirmed in written form by the manufacturer. Our general terms and conditions apply in all cases. All previous data sheets are invalid with the publication of this data sheet. Please note our handling and storage instructions as well accessible at [www.shieldex.de](http://www.shieldex.de).