



Shieldex® Med-tex P130

1150902130

Raw Material	78 % Polyamide + 22 % Elastomer
Type of knit	Stretch-Tricot
Metal Plated	Silver
Material Composition	(63 % PA /18 % EL / 19 % Ag) ± 10 %
Stretch	Double stretch direction / elongation warp 55- 205 % / weft 85-125 %
Abrasion Resistance	≤ 9000 cycles
Total Weight	130 g/m ² ± 18 %
Total Thickness	0.55 mm ± 15 %
Roll Width	132 ± 5 cm
Roll Length	Max. 36 m
Temperature Range	-30 °C to 80 °C
Storage and Handling	According to our care and handling instructions
Compliance and Certification	OEKO-TEX® STANDARD 100, DIN EN ISO 9001:2015, REACH, RoHS, Screening test using a praxis-near carrier test system following ISO 18184:2019 against the Bovine Coronavirus

Alterations Reserved 01.01.22/18 – The above information has been compiled from our manufacturer area according to the latest state of development and application technology. Since application and further processing are beyond our control, no liability of the producer can be derived from the contents of the data sheet. All deviant or transcending data sheet information must be confirmed in written form by the manufacturer. Our general terms and conditions apply in all cases. All previous data sheets are invalid with the publication of this data sheet. Please note our handling and storage instructions as well accessible at www.shieldex.de.