shieldex

Ag	Cu	Ni	Sn

Shieldex®
117/17 2-ply HC + B

260121011717HC

Material	Polyamide / Nylon 6.6
Metal Plated	99.9 % Pure Silver
+ B Coating	Nitrile rubber as additional protective coating
Yarn count silverized	295 ± 3 dtex
Twist	Z 550
Electrical Resistivity	< 300 Ω/m
Yield	33.800 m/kg ± 3 %
Tenacity	44 ± 5 cN/tex
Elongation / Break	21 % ± 5
Make Up	On cones 230 mm 3° 30
Packaging	Average 450 g net yarn per cone 15 or 30 cones per carton
Storage and Handling	According to our care and handling instructions
Compliance and Certification	OEKO-TEX® Standard 100, DIN EN ISO 9001:2015, REACH, RoHS

Alterations Reserved 01.05.21/06 – The above information has been compiled from our manufacturer area according to the latest state of development and application technology. Since application and further processing are beyond our control, no liability of the producer can be derived from the contents of the data sheet. All deviant or transcending data sheet information must be confirmed in written form by the manufacturer. Our general terms and conditions apply in all cases. All previous data sheets are invalid with the publication of this data sheet. Please note our handling and storage instructions as well accessible at www.shieldex.de.

Statex Produktions- und Vertriebs GmbH
Kleiner Ort 9-11
28357 Bremen, Germany

Contact
Tel. +49 421 27 50 47
Fax +49 421 27 36 43
info@shieldex.de

OEKO-TEX®
CONFIDENCE IN TEXTILES
STANDARD 100
A03-0143 HOHENSTEIN HTTI
Tested for harmful substances
www.oeko-tex.com/standard100